

## D550 Series C-band Downconverters

INPUT SPECIFICATION		Options
1. Frequency range:	3.4 to 4.8GHz (check model table)	
2. Connector:	N-type	SMA
3. Impedance:	50Ω	
4. Return loss:	≥18dB	
OUTPUT SPECIFICATION		
5. Frequency range:	70 ± 20MHz or 140 ± 40MHz (check model table)	
6. Connector:	BNC	
7. Impedance:	50Ω	75Ω
8. Return loss:	≥15dB	
9. 1dB compression point:	+10dBm	
10. Third order intercept::	+20dBm	
TRANSFER CHARACTERISTICS		
11. Gain:	30 to 50dB, adjustable in 0.1dB steps	
12. Gain ripple:	over ±20MHz: ≤1dB p.t.p. over ±40MHz: ≤1.5dB p.t.p. over input band: ≤3dB p.t.p	
13. Group delay distortion:	over ±5MHz <2ns over ±20MHz <5ns	
14. Gain stability, 0°C to 50°C:	±1dB	
15. Frequency stability, 0°C to 50°C:	0°C to +50°C: < 3 x 10 <sup>-8</sup> At constant temperature over 24 hr: < 5 x 10 <sup>-9</sup> Aging per year: < 5 x 10 <sup>-7</sup>	
16. External reference:	10MHz, 0dBm	5MHz, 0dBm
17. Synthesiser step size:	1kHz	
18. Noise figure (full gain):	<17dB	
Spurii		
19. Image rejection:	≥50dB	
20. In-band spurii (at 0dBm output):	<-60dBc	
PHASE NOISE		
21. 10Hz:	<-45dBc/Hz	
22. 100Hz:	<-70dBc/Hz	
23. 1kHz:	<-80dBc/Hz	
24. 10kHz:	<-85dBc/Hz	
25. 100kHz:	<-95dBc/Hz	
26. 1MHz:	<-110dBc/Hz	
27. Mains related:	<-50dBc	
MISCELLANEOUS		
28. Power supply:	115V/230V ±10% 50/60Hz ±10%, 45VA	
29. Mechanical:	1U 19" frame, 400mm deep	
30. Temperature:	Operating: 0° to 50°C Storage: -40° to 85°C	
31. Relative humidity:	Operating: 0 to 90% Storage: 0 to 95%	
32. Summary alarm:	NO and NC dry relay contacts via rear mounted connector	
33. Summary alarm indication:	Front panel LED	
34. Remote control:	<ul style="list-style-type: none"> <li>● RS232 or RS422/RS485, connector D-type 9P F</li> <li>● Serial emulation over TCP/IP, connector RJ45</li> <li>● SNMP and HTTP over TCP/IP Ethernet, connector RJ45</li> </ul>	

### MODEL TABLE

Input Frequency	Output frequency and bandwidth		
	70 ± 20MHz	140 ± 40MHz	70 ± 20MHz, 140 ± 40MHz
3.625 - 4.2	D550	D555	D570
3.4 - 4.2	D551	D556	D571
4.5 - 4.8	D552	D557	D572
3.4 - 4.2 4.5 - 4.8	D553	D558	D573
3.4 - 4.8	D554	D559	D574
4.45 - 4.95	D580	D585	D587